

# SAFETY DATA SHEETS

According to the UN GHS revision 10

## 1: Identification

### 1.1 GHS Product identifier

**Product name** m-Toluidine

### 1.2 Other means of identification

**Product number** 108-44-1

**Other names** m-Toluidine

### 1.3 Recommended use of the chemical and restrictions on use

**Identified uses** Industrial and scientific research use.

**Uses advised against** no data available

### 1.4 Supplier's details

**Company** Zhongshan Greenrock Technology Co., Ltd.

**Address** No. 138, Jinsan Avenue, Sanjiao Town, Zhongshan City, Guangdong Province, China

**Telephone** +86-2087066781

### 1.5 Emergency phone number

**Emergency phone number** +86-2087066781

**Service hours** Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).

## 2: Hazard identification

### 2.1 Emergency Overview

Highly toxic substances, even small amounts of which can cause death or serious health effects. They can enter the body through inhalation, skin contact, or ingestion. Immediate protective measures must be taken to avoid any contact.

### 2.2 GHS Classification

Acute toxicity, oral; acute toxicity, dermal; acute toxicity, inhalation : Category 3

Acute toxicity, oral : Category 3

Acute toxicity, dermal : Category 3

Serious eye damage/eye irritation : Category 2A

Acute toxicity, inhalation : Category 3

Specific target organ toxicity, repeated exposure : Category 2

Hazardous to the aquatic environment, acute hazard : Category 1

Hazardous to the aquatic environment, long-term hazard : Category 1

## 2.3 GHS label elements, including precautionary statements

**Pictogram(s)**



**Signal word**

Danger

**Hazard statement(s)**

H301+H311+H331 Toxic if swallowed, in contact with skin or if inhaled  
H301 Toxic if swallowed  
H311 Toxic in contact with skin  
H319 Causes serious eye irritation  
H331 Toxic if inhaled  
H373 May cause damage to organs through prolonged or repeated exposure  
H400 Very toxic to aquatic life  
H410 Very toxic to aquatic life with long lasting effects

**Precautionary statement(s)**

**Prevention**

P260 Do not breathe dust/fume/gas/mist/vapors/spray.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P264 Wash hands [and ...] thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...  
P264+P265 Wash hands [and ...] thoroughly after handling. Do not touch eyes.

**Response**

P316 Get emergency medical help immediately.  
P319 Get medical help if you feel unwell.  
P321 Specific treatment (see ... on this label).  
P330 Rinse mouth.  
P391 Collect spillage.  
P301+P316 IF SWALLOWED, Get emergency medical help immediately.  
P302+P352 IF ON SKIN, wash with plenty of water/...  
P304+P340 IF INHALED, Remove person to fresh air and keep comfortable for breathing.  
P305+P351+P338 IF IN EYES, Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.  
P337+P317 If eye irritation persists, Get medical help.  
P361+P364 Take off immediately all contaminated clothing and wash it before reuse.

**Storage**

P405 Store locked up.  
P403+P233 Store in a well-ventilated place. Keep container tightly closed.

**Disposal**

P501 Dispose of contents/container to ...

## 2.4 Physical and chemical

Some substances may also be flammable or corrosive. Mixing with other substances may produce toxic products. Highly volatile substances can form toxic vapor clouds, expanding the hazard range.

## 2.5 Health hazards

Acute toxicity, May cause respiratory failure, cardiac arrest, nervous system depression, or organ failure. Severe symptoms may appear within a short period of exposure (minutes to hours). Long-term effects may include permanent organ damage.

## 2.6 Environmental hazards

It is extremely toxic to aquatic organisms and terrestrial ecosystems, and even a small release can cause large-scale biological mortality. It may persist in the environment and accumulate through the food chain, causing long-term damage to ecosystems.

## 2.7 Other hazards which do not result in classification

no data available

# 3: Composition/information on ingredients

## 3.1 Substances

Chemical name	Common names and synonyms	CAS number	EC number	Concentration
m-Toluidine	m-Toluidine	108-44-1	203-583-1	99%

# 4: First-aid measures

## 4.1 General advice

Stop contact immediately and move to a safe area; bring the material SDS document and call emergency services immediately; record the route of exposure (inhalation/skin/ingestion), exposure time and dosage for the doctor's judgment.

## 4.2 If inhaled

Quickly transfer the patient to a place with fresh air, keep the patient lying flat with the head tilted to one side (to prevent suffocation by vomitus); if cyanosis or breathing difficulties occur, immediately give oxygen (flow rate 5-10L/min); it is strictly forbidden to feed/drink water to the unconscious person, and seek medical attention immediately.

## 4.3 In case of skin contact

Immediately remove contaminated clothing (if clothing is stuck to the skin, cut it with scissors to avoid tearing it). Rinse the affected area with plenty of running water for 20-30 minutes (the water temperature should be around 37°C, avoiding excessive heat or cold). If the skin is damaged, cover it with sterile gauze after rinsing. Do not apply ointment.

## 4.4 In case of eye contact

Immediately flush with an eyewash station for 15 minutes (open the eyelids to ensure thorough flushing of the upper and lower fornixes); wear a light-shielding eye mask after flushing to avoid strong light

stimulation, and immediately seek medical attention from an ophthalmologist (bring along the substance SDS).

#### **4.5 If swallowed**

Self-induced vomiting is strictly prohibited (especially with corrosive and toxic substances, which may cause secondary burns to the esophagus). If the patient is conscious and not convulsing, they can drink 50-100ml of milk under the guidance of a doctor (to protect the gastric mucosa).

#### **4.6 Most important symptoms and effects, both acute and delayed**

Acute symptoms: nausea and vomiting, abdominal pain, dyspnea, convulsions, confusion, and decreased blood pressure; delayed symptoms: liver and kidney damage (appearing within 24-72 hours), methemoglobinemia (such as nitrite poisoning).

#### **4.7 Protection of first-aiders**

Rescuers must wear fully enclosed chemical protective clothing, a gas mask (with a targeted gas filter cartridge, such as for organic vapors and acid gases), and chemical protective gloves; avoid direct contact with the patient's vomitus/secretions, and wash hands immediately with chlorine-containing disinfectant after contact.

#### **4.8 Notes to physician**

Inform the physician of the substance's toxicity (e.g., oral LD50 = 5 mg/kg) and route of exposure; prioritize gastric lavage (physician evaluation required for appropriateness) and administer antidotes (e.g., atropine for organophosphate poisoning); monitor liver and kidney function, electrolytes, and coagulation function.

## **5: Fire-fighting measures**

### **5.1 Unsuitable extinguishing media**

It is strictly forbidden to use fire extinguishing agents that may cause the spread of toxic substances (such as high-pressure water jets); if flammable liquids are involved, avoid using carbon dioxide (which may cause toxic vapor condensation).

### **5.2 Specific hazards during fire fighting**

Combustion may be accompanied by the release of highly toxic substances (such as cyanide and arsenide), which are fatal by inhalation or skin contact; the combustion of flammable components can easily cause explosions and intensify the spread of toxic substances; toxic vapors are heavier than air and tend to accumulate in low-lying areas.

### **5.3 Hazardous combustion products**

Highly toxic gases (such as hydrogen chloride, hydrogen fluoride, phosgene), carbon monoxide, nitrogen oxides; some contain heavy metal components that release toxic fumes such as mercury and lead.

### **5.4 Specific extinguishing methods**

For small areas: use dry powder fire extinguishing agent to extinguish the fire, and dilute the toxic vapor with mist water (avoid direct spraying); for large areas: give priority to evacuation. If fire extinguishing is necessary, set up a fire extinguishing point upwind and cover it with foam (to isolate oxygen); after

extinguishing the fire, test the area for toxicity concentration (entry is allowed only when the value is below MAC).

## **5.5 Special protective equipment for fire-fighters**

Wear fully enclosed chemical protective clothing, gas masks (with targeted gas filter boxes, such as organic vapor + acidic gas), and chemical protective gloves (made of fluororubber); carry a portable toxic gas detector; equipment must be disinfected after the operation, and personnel must undergo health monitoring.

# **6: Accidental release measures**

## **6.1 Protective measures for workers**

Wear fully enclosed chemical protective clothing, positive pressure air respirator, chemical protective gloves (toxic-resistant type) and goggles; avoid direct contact with the skin and wash immediately after work.

## **6.2 Environmental protection measure**

Isolate the 30-meter contaminated area to prevent the leak from spreading through rainwater/groundwater; take samples of water/soil for testing, and use activated carbon adsorption (organic poison) or neutralizer (inorganic poison) for treatment when exceeding the standard; strictly prohibit the leak from entering the drinking water source.

## **6.3 Containment methods for leaked chemicals**

Collect liquids in corrosion-resistant sealed containers (marked with "toxic substances"); collect solids in chemical-resistant bags (to avoid dust); and store them separately in a hazardous waste warehouse after collection, away from food/feed.

## **6.4 Cleanup methods for chemical spills**

Small leakage: absorb with special absorbent cotton (toxic-resistant) and put into chemical-proof bag; large leakage: professionals use chemical-proof pump to transfer to special storage tank; after cleaning, treat the ground with neutralizer (weak base for acid poison and weak acid for alkali poison).

## **6.5 Measures to prevent the spread of leaks**

Set up a 30-meter isolation zone and prohibit unauthorized personnel from entering; volatile toxic substances require explosion-proof ventilation to reduce gas concentration; use chemical defense isolation belts to block them, and focus on monitoring low-lying areas (to prevent the accumulation of toxic substances).

## **6.6 Container leakage treatment**

Minor leaks: Seal with compatible sealant; Serious leaks: Evacuate immediately, close the upstream valve (if safe), and have the toxic material disposal team handle it. It is strictly forbidden to open the container without authorization.

## **6.7 Special considerations**

Workers must receive poisoning first aid training and carry antidotes (if applicable). In case of skin contact, flush immediately with plenty of water for 15 minutes. In case of inhalation poisoning, move immediately to fresh air and seek medical attention.

## 7: Handling and storage

### 7.1 Safe storage conditions

Store in a closed, impermeable dedicated warehouse (the walls are made of anti-corrosion materials, such as polyethylene coating); the container is made of corrosion-resistant material (such as polytetrafluoroethylene, glass-lined steel), with a double sealing cover (threaded cover + nitrile rubber sealing ring); the warehouse is equipped with a negative pressure ventilation system (air changes ? 8 times/hour), and the exhaust gas must be treated with activated carbon adsorption (adsorption efficiency ? 95%).

### 7.2 Storage precautions

Store them separately from food, feed, and medicine (isolation distance ? 3 meters), and strictly prohibit them from being adjacent to drinking water sources; clearly mark "highly toxic" and H code on container labels and store them separately on locked shelves; check the sealing of containers weekly and immediately transfer them to the emergency treatment area if any leakage is found; workers must wear fully enclosed chemical protective clothing before entering the warehouse.

### 7.3 VCI Storage Grade

Level 1 (highest): The inner wall of the metal container is coated with a VCI anti-rust coating (thickness ? 50?m), and the outer surface of the container is wrapped with a vapor phase anti-rust film; the concentration of toxic substances in the warehouse is tested monthly to ensure that it is lower than the MAC value (for example, MAC of oral toxic substances ? 0.1mg/m<sup>3</sup>).

### 7.4 Recommended storage temperature

10-30?, avoid extreme temperatures (below 0? or above 35?); volatile toxic substances must be kept at a temperature ?25? to reduce vapor release; refrigerated storage substances (such as certain biotoxins) must be maintained at 2-8? and equipped with dual power supply protection (if the label has a recommended storage temperature, the label shall prevail).

### 7.5 Handling

For precautions see Safety Data Sheet section 2  
Advice on safe handling : Work under hood. Do not inhale substance/mixture.

## 8: Exposure controls/personal protection

### 8.1 Respiratory protection

Choose according to the exposure route: volatile substances require positive pressure air respirators; dust/aerosols require powered air-purifying respirators to ensure the protection factor (APF) ? 1000.

### 8.2 Recommended Filter type

For organic toxic substances, choose Type A filter cartridge (to protect against organic vapors, such as benzene and methanol); for inorganic toxic substances, choose Type B (to protect against ammonia) or Type E (to protect against acidic gases, such as hydrogen chloride); for dust, add Type P3 filter cotton.

### 8.3 Eye/face protection

Wear a full-face chemical protective mask. The mask material must be resistant to toxic penetration (such as fluororubber), and the lens must be anti-fog and anti-chemical corrosion.

### 8.4 Skin and body protection

Wear fully enclosed chemical protective clothing. The material must be compatible with toxic substances (such as polyethylene + neoprene composite material); the cuffs and ankles must be tightened and equipped with emergency escape zippers.

### 8.5 Hand protection

Wear toxic and chemical-resistant gloves, preferably made of fluororubber or butyl rubber, with a length of 30 cm, covering the forearm, and change every 4 hours

### 8.6 Hygiene measures

Immediately after the operation, clean the skin with a special detergent (such as a weak alkaline detergent), and then rinse with running water for 15 minutes; clothes need to be disinfected at high temperature (above 60°C) before washing; regular physical examinations (blood routine, liver and kidney function tests every 3 months).

## 9: Physical and chemical properties and safety characteristics

<b>Physical state</b>	Colorless oily liquid
<b>Colour</b>	Colorless to light yellow liquid
<b>Odour</b>	Aromatic, amine-like odor
<b>Melting point/freezing point</b>	-30oC
<b>Boiling point or initial boiling point and boiling range</b>	203-204oC
<b>Flammability</b>	Class IIIA Combustible Liquid: Fl.P. at or above 60°C and below 93.33°C. Combustible. Gives off irritating or toxic fumes (or gases) in a fire.
<b>Lower and upper explosion limit/flammability limit</b>	no data available
<b>Flash point</b>	86oC
<b>Auto-ignition temperature</b>	481.67°C (USCG, 1999)
<b>Decomposition temperature</b>	When heated to decomposition it emits highly toxic fumes of /nitroxides/.
<b>pH</b>	7 (H <sub>2</sub> O, 20?)
<b>Kinematic viscosity</b>	3.306 mPa·sec at 25°C
<b>Solubility</b>	In water: 0.2 g/100 mL (20 oC)

<b>Partition coefficient n-octanol/water</b>	log Kow = 1.40
<b>Vapour pressure</b>	0.278mmHg at 25°C
<b>Density and/or relative density</b>	0.989
<b>Relative vapour density</b>	3.90 (Air = 1)
<b>Particle characteristics</b>	no data available

## 10: Stability and reactivity

### 10.1 Reactivity

no data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### 10.3 Possibility of hazardous reactions

Flammable when exposed to heat or flame. As a result of flow, agitation, etc., electrostatic charges can be generated. M-TOLUIDINE neutralizes acids in exothermic reactions to form salts plus water. May be incompatible with isocyanates, halogenated organics, peroxides, phenols (acidic), epoxides, anhydrides, and acid halides. May generate hydrogen, a flammable gas, in combination with strong reducing agents such as hydrides. Can react vigorously with oxidizing reagents. Emits toxic fumes of oxides of nitrogen when heated to decomposition [Lewis, 3rd ed., 1993, p. 1253].

### 10.4 Conditions to avoid

no data available

### 10.5 Incompatible materials

Can react vigorously on contact with oxidizing materials.

### 10.6 Hazardous decomposition products

When heated to decomposition it emits highly toxic fumes of /nitroxides/.

## 11: Toxicological information

### 11.1 Acute toxicity

Oral: LD50 Rat oral 450 mg/kg

Inhalation: no data available

Dermal: no data available

## **11.2 Skin corrosion/irritation**

no data available

## **11.3 Serious eye damage/irritation**

no data available

## **11.4 Respiratory or skin sensitization**

no data available

## **11.5 Germ cell mutagenicity**

no data available

## **11.6 Carcinogenicity**

A4; Not classifiable as a human carcinogen.

## **11.7 Reproductive toxicity**

no data available

## **11.8 STOT-single exposure**

no data available

## **11.9 STOT-repeated exposure**

no data available

## **11.10 Aspiration hazard**

no data available

# **12: Ecological information**

## **12.1 Toxicity**

Toxicity to fish: no data available

Toxicity to daphnia and other aquatic invertebrates: LC50; Species: Daphnia magna (water flea);

Conditions: static; Concentration: 0.73 mg/L for 24 hr

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

## **12.2 Persistence and degradability**

AEROBIC: 3-Aminotoluene, present at 100 mg/L, reached 0% of its theoretical BOD in 4 weeks using an activated sludge inoculum at 30 mg/L in the Japanese MITI test(1). In other screening tests, 3-aminotoluene was found to be readily biodegradable(2-4). In one test, 74% of theoretical BOD was achieved in 7.5 days with an activated sludge inoculum acclimated to aniline(2). In another, 97.7% degradation occurred in 5 days with an activated sludge inoculum(3). Complete degradation of 3-aminotoluene was obtained within 8 days with a soil inoculum(4). The half-life of 3-aminotoluene in

natural water from ponds and rivers in which the microbial populations were increased 10- to 100-fold by filtration and nutrient addition was 4 hours(5). 3-Aminotoluene, present at 2 mg/L, reached 50% of its theoretical BOD in 5 days using water from the Songhua River in China as an inoculum(6).

### 12.3 Bioaccumulative potential

An estimated BCF of 3.9 was calculated for 3-aminotoluene(SRC), using a log Kow of 1.40(1) and a regression-derived equation(2). According to a classification scheme(3), this BCF suggests the potential for bioconcentration in aquatic organisms is low(SRC).

### 12.4 Mobility in soil

The mean Koc of 3-aminotoluene in 4 silt loam soils was 44 over a pH range of 6.1 to 7.5(1). According to a classification scheme(2), this Koc value suggests that 3-aminotoluene is expected to have very high mobility in soil. The pKa of 3-aminotoluene is 4.69(3), indicating that this compound will partially exist in cation form in the environment and cations generally adsorb more strongly to soils containing organic carbon and clay than their neutral counterparts(4). Aromatic amines are expected to bind strongly to humus or organic matter in soils due to the high reactivity of the aromatic amino group(5,6), suggesting that mobility of the neutral species may be much lower in some soils(SRC).

### 12.5 Other adverse effects

no data available

## 13: Disposal considerations

### 13.1 Disposal methods for waste chemicals

This must be handled by a qualified unit that handles highly toxic waste, using high-temperature incineration (800-1000°C) or chemical neutralization (such as oxidative decomposition) to completely destroy the toxicity. Liquid highly toxic substances must be solidified before incineration. Those that cannot be incinerated must be stabilized/solidified before being safely landfilled.

### 13.2 Precautions

Disposal personnel must wear fully enclosed chemical protective suits and positive pressure respirators; waste must be strictly classified and packaged to prevent leakage; exhaust gas and wastewater generated during the disposal process must meet discharge standards; mixing with other types of waste is prohibited; and disposal records must be kept for at least 10 years for traceability.

## 14: Transport information

### 14.1 UN Number

ADR/RID: UN1708

IMDG: UN1708

IATA: UN1708

### 14.2 UN Proper Shipping Name

ADR/RID: TOLUIDINES, LIQUID      IMDG: TOLUIDINES, LIQUID      IATA: TOLUIDINES, LIQUID

### 14.3 Transport hazard class(es)

ADR/RID: 6.1      IMDG: 6.1      IATA: 6.1

### 14.4 Packing group, if applicable

ADR/RID: II      IMDG: II      IATA: II

### 14.5 Environmental hazards

ADR/RID: yes      IMDG: yes      IATA: yes

### 14.6 Special precautions for user

no data available

### 14.7 Transport in bulk according to IMO instruments

no data available

## 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

Chemical name	Common names and synonyms	CAS number	EC number
m-Toluidine	m-Toluidine	108-44-1	203-583-1
New Zealand Inventory of Chemicals (NZIoC)			Listed.
Philippines Inventory of Chemicals and Chemical Substances (PICCS)			Listed.
Vietnam National Chemical Inventory			Not Listed.
Australian Inventory of Industrial Chemicals (AIIC)			Not Listed.
Catalogue of Strictly Restricted Toxic Chemicals in China			Not Listed.
China Catalog of Hazardous chemicals 2015			Listed.
European INventory of Existing Commercial chemical Substances			Not Listed.
IARC Monographs on the Evaluation of Carcinogenic Risks to Humans			Not Listed.
TSCA Inventory of Chemical Substances			Listed.

## 16: Other information

### Information on revision

SDS Creation Date      July 1, 2025

SDS Revision Date      July 1, 2025

## Abbreviations and acronyms in SDS

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

## SDS References

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: [http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

**Any questions regarding this Safety Data Sheet, Please send your inquiry to [sales@MolBest.com](mailto:sales@MolBest.com)**

---

*Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any damage resulting from handling or from contact with the above product.*