

# SAFETY DATA SHEETS

According to the UN GHS revision 10

## 1: Identification

### 1.1 GHS Product identifier

**Product name** 1,3-Propane sultone

### 1.2 Other means of identification

**Product number** 1120-71-4

**Other names** 1,3-Propane sultone

### 1.3 Recommended use of the chemical and restrictions on use

**Identified uses** Industrial and scientific research use.

**Uses advised against** no data available

### 1.4 Supplier's details

**Company** Zhongshan Greenrock Technology Co., Ltd.

**Address** No. 138, Jinsan Avenue, Sanjiao Town, Zhongshan City, Guangdong Province, China

**Telephone** +86-2087066781

### 1.5 Emergency phone number

**Emergency phone number** +86-2087066781

**Service hours** Monday to Friday, 9am-5pm (Standard time zone: UTC/GMT +8 hours).

## 2: Hazard identification

### 2.1 Emergency Overview

Highly toxic substances, even small amounts of which can cause death or serious health effects. They can enter the body through inhalation, skin contact, or ingestion. Immediate protective measures must be taken to avoid any contact.

### 2.2 GHS Classification

Acute toxicity, oral; acute toxicity, dermal : Category 3

Acute toxicity, oral : Category 3

Acute toxicity, oral : Category 4

Acute toxicity, dermal : Category 3

Acute toxicity, dermal : Category 4

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Serious eye damage/eye irritation : Category 2A

Acute toxicity, inhalation : Category 4

Germ cell mutagenicity : Category 2

Carcinogenicity : Category 1, 1A, 1B

Hazardous to the aquatic environment, long-term hazard : Category 3

## 2.3 GHS label elements, including precautionary statements

**Pictogram(s)**



**Signal word**

Danger

**Hazard statement(s)**

H301+H311 Toxic if swallowed or in contact with skin  
H301 Toxic if swallowed  
H302 Harmful if swallowed  
H311 Toxic in contact with skin  
H312 Harmful in contact with skin  
H315 Causes skin irritation  
H318 Causes serious eye damage  
H319 Causes serious eye irritation  
H332 Harmful if inhaled  
H341 Suspected of causing genetic defects  
H350 May cause cancer  
H412 Harmful to aquatic life with long lasting effects

**Precautionary statement(s)**

**Prevention**

P203 Obtain, read and follow all safety instructions before use.  
P261 Avoid breathing dust/fume/gas/mist/vapors/spray.  
P262 Do not get in eyes, on skin, or on clothing.  
P264 Wash hands [and ...] thoroughly after handling.  
P270 Do not eat, drink or smoke when using this product.  
P271 Use only outdoors or in a well-ventilated area.  
P273 Avoid release to the environment.  
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/...  
P264+P265 Wash hands [and ...] thoroughly after handling. Do not touch eyes.

<b>Response</b>	<p>P316 Get emergency medical help immediately.</p> <p>P317 Get emergency medical help.</p> <p>P318 if exposed or concerned, get medical advice.</p> <p>P321 Specific treatment (see ... on this label).</p> <p>P330 Rinse mouth.</p> <p>P301+P316 IF SWALLOWED,Get emergency medical help immediately.</p> <p>P301+P317 IF SWALLOWED,Get medical help.</p> <p>P302+P352 IF ON SKIN,wash with plenty of water/...</p> <p>P304+P340 IF INHALED,Remove person to fresh air and keep comfortable for breathing.</p> <p>P305+P351+P338 IF IN EYES,Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.</p> <p>P305+P354+P338 IF IN EYES,Immediately rinse with water for several minutes. Remove contact lenses if present and easy to do. Continue rinsing.</p> <p>P332+P317 If skin irritation occurs,Get medical help.</p> <p>P337+P317 If eye irritation persists,Get medical help.</p> <p>P361+P364 Take off immediately all contaminated clothing and wash it before reuse.</p> <p>P362+P364 Take off contaminated clothing and wash it before reuse.</p>
<b>Storage</b>	P405 Store locked up.
<b>Disposal</b>	P501 Dispose of contents/container to ...

## 2.4 Physical and chemical

Some substances may also be flammable or corrosive. Mixing with other substances may produce toxic products. Highly volatile substances can form toxic vapor clouds, expanding the hazard range.

## 2.5 Health hazards

Acute toxicity,May cause respiratory failure, cardiac arrest, nervous system depression, or organ failure. Severe symptoms may appear within a short period of exposure (minutes to hours). Long-term effects may include permanent organ damage.

## 2.6 Environmental hazards

It is extremely toxic to aquatic organisms and terrestrial ecosystems, and even a small release can cause large-scale biological mortality. It may persist in the environment and accumulate through the food chain, causing long-term damage to ecosystems.

## 2.7 Other hazards which do not result in classification

no data available

# 3: Composition/information on ingredients

## 3.1 Substances

Chemical name	Common names and synonyms	CAS number	EC number	Concentration
1,3-Propane sultone	1,3-Propane sultone	1120-71-4	214-317-9	99%

## 4: First-aid measures

### 4.1 General advice

Stop contact immediately and move to a safe area; bring the material SDS document and call emergency services immediately; record the route of exposure (inhalation/skin/ingestion), exposure time and dosage for the doctor's judgment.

### 4.2 If inhaled

Quickly transfer the patient to a place with fresh air, keep the patient lying flat with the head tilted to one side (to prevent suffocation by vomitus); if cyanosis or breathing difficulties occur, immediately give oxygen (flow rate 5-10L/min); it is strictly forbidden to feed/drink water to the unconscious person, and seek medical attention immediately.

### 4.3 In case of skin contact

Immediately remove contaminated clothing (if clothing is stuck to the skin, cut it with scissors to avoid tearing it). Rinse the affected area with plenty of running water for 20-30 minutes (the water temperature should be around 37°C, avoiding excessive heat or cold). If the skin is damaged, cover it with sterile gauze after rinsing. Do not apply ointment.

### 4.4 In case of eye contact

Immediately flush with an eyewash station for 15 minutes (open the eyelids to ensure thorough flushing of the upper and lower fornixes); wear a light-shielding eye mask after flushing to avoid strong light stimulation, and immediately seek medical attention from an ophthalmologist (bring along the substance SDS).

### 4.5 If swallowed

Self-induced vomiting is strictly prohibited (especially with corrosive and toxic substances, which may cause secondary burns to the esophagus). If the patient is conscious and not convulsing, they can drink 50-100ml of milk under the guidance of a doctor (to protect the gastric mucosa).

### 4.6 Most important symptoms and effects, both acute and delayed

Acute symptoms: nausea and vomiting, abdominal pain, dyspnea, convulsions, confusion, and decreased blood pressure; delayed symptoms: liver and kidney damage (appearing within 24-72 hours), methemoglobinemia (such as nitrite poisoning).

### 4.7 Protection of first-aiders

Rescuers must wear fully enclosed chemical protective clothing, a gas mask (with a targeted gas filter cartridge, such as for organic vapors and acid gases), and chemical protective gloves; avoid direct contact with the patient's vomitus/secretions, and wash hands immediately with chlorine-containing disinfectant after contact.

### 4.8 Notes to physician

Inform the physician of the substance's toxicity (e.g., oral LD50 = 5 mg/kg) and route of exposure; prioritize gastric lavage (physician evaluation required for appropriateness) and administer antidotes (e.g., atropine for organophosphate poisoning); monitor liver and kidney function, electrolytes, and coagulation function.

## **5: Fire-fighting measures**

### **5.1 Unsuitable extinguishing media**

It is strictly forbidden to use fire extinguishing agents that may cause the spread of toxic substances (such as high-pressure water jets); if flammable liquids are involved, avoid using carbon dioxide (which may cause toxic vapor condensation).

### **5.2 Specific hazards during fire fighting**

Combustion may be accompanied by the release of highly toxic substances (such as cyanide and arsenide), which are fatal by inhalation or skin contact; the combustion of flammable components can easily cause explosions and intensify the spread of toxic substances; toxic vapors are heavier than air and tend to accumulate in low-lying areas.

### **5.3 Hazardous combustion products**

Highly toxic gases (such as hydrogen chloride, hydrogen fluoride, phosgene), carbon monoxide, nitrogen oxides; some contain heavy metal components that release toxic fumes such as mercury and lead.

### **5.4 Specific extinguishing methods**

For small areas: use dry powder fire extinguishing agent to extinguish the fire, and dilute the toxic vapor with mist water (avoid direct spraying); for large areas: give priority to evacuation. If fire extinguishing is necessary, set up a fire extinguishing point upwind and cover it with foam (to isolate oxygen); after extinguishing the fire, test the area for toxicity concentration (entry is allowed only when the value is below MAC).

### **5.5 Special protective equipment for fire-fighters**

Wear fully enclosed chemical protective clothing, gas masks (with targeted gas filter boxes, such as organic vapor + acidic gas), and chemical protective gloves (made of fluororubber); carry a portable toxic gas detector; equipment must be disinfected after the operation, and personnel must undergo health monitoring.

## **6: Accidental release measures**

### **6.1 Protective measures for workers**

Wear fully enclosed chemical protective clothing, positive pressure air respirator, chemical protective gloves (toxic-resistant type) and goggles; avoid direct contact with the skin and wash immediately after work.

### **6.2 Environmental protection measure**

Isolate the 30-meter contaminated area to prevent the leak from spreading through rainwater/groundwater; take samples of water/soil for testing, and use activated carbon adsorption (organic poison) or neutralizer (inorganic poison) for treatment when exceeding the standard; strictly prohibit the leak from entering the drinking water source.

### **6.3 Containment methods for leaked chemicals**

Collect liquids in corrosion-resistant sealed containers (marked with "toxic substances"); collect solids in chemical-resistant bags (to avoid dust); and store them separately in a hazardous waste warehouse after collection, away from food/feed.

## 6.4 Cleanup methods for chemical spills

Small leakage: absorb with special absorbent cotton (toxic-resistant) and put into chemical-proof bag; large leakage: professionals use chemical-proof pump to transfer to special storage tank; after cleaning, treat the ground with neutralizer (weak base for acid poison and weak acid for alkali poison).

## 6.5 Measures to prevent the spread of leaks

Set up a 30-meter isolation zone and prohibit unauthorized personnel from entering; volatile toxic substances require explosion-proof ventilation to reduce gas concentration; use chemical defense isolation belts to block them, and focus on monitoring low-lying areas (to prevent the accumulation of toxic substances).

## 6.6 Container leakage treatment

Minor leaks: Seal with compatible sealant; Serious leaks: Evacuate immediately, close the upstream valve (if safe), and have the toxic material disposal team handle it. It is strictly forbidden to open the container without authorization.

## 6.7 Special considerations

Workers must receive poisoning first aid training and carry antidotes (if applicable). In case of skin contact, flush immediately with plenty of water for 15 minutes. In case of inhalation poisoning, move immediately to fresh air and seek medical attention.

# 7: Handling and storage

## 7.1 Safe storage conditions

Store in a closed, impermeable dedicated warehouse (the walls are made of anti-corrosion materials, such as polyethylene coating); the container is made of corrosion-resistant material (such as polytetrafluoroethylene, glass-lined steel), with a double sealing cover (threaded cover + nitrile rubber sealing ring); the warehouse is equipped with a negative pressure ventilation system (air changes ? 8 times/hour), and the exhaust gas must be treated with activated carbon adsorption (adsorption efficiency ? 95%).

## 7.2 Storage precautions

Store them separately from food, feed, and medicine (isolation distance ? 3 meters), and strictly prohibit them from being adjacent to drinking water sources; clearly mark "highly toxic" and H code on container labels and store them separately on locked shelves; check the sealing of containers weekly and immediately transfer them to the emergency treatment area if any leakage is found; workers must wear fully enclosed chemical protective clothing before entering the warehouse.

## 7.3 VCI Storage Grade

Level 1 (highest): The inner wall of the metal container is coated with a VCI anti-rust coating (thickness ? 50?m), and the outer surface of the container is wrapped with a vapor phase anti-rust film; the concentration of toxic substances in the warehouse is tested monthly to ensure that it is lower than the

MAC value (for example, MAC of oral toxic substances  $\geq 0.1\text{mg}/\text{m}^3$ ).

## 7.4 Recommended storage temperature

10-30°C, avoid extreme temperatures (below 0°C or above 35°C); volatile toxic substances must be kept at a temperature  $\approx 25^\circ\text{C}$  to reduce vapor release; refrigerated storage substances (such as certain biotoxins) must be maintained at 2-8°C and equipped with dual power supply protection (if the label has a recommended storage temperature, the label shall prevail).

## 7.5 Handling

For precautions see Safety Data Sheet section 2

Advice on safe handling : Work under hood. Do not inhale substance/mixture.

# 8: Exposure controls/personal protection

## 8.1 Respiratory protection

Choose according to the exposure route: volatile substances require positive pressure air respirators; dust/aerosols require powered air-purifying respirators to ensure the protection factor (APF)  $\geq 1000$ .

## 8.2 Recommended Filter type

For organic toxic substances, choose Type A filter cartridge (to protect against organic vapors, such as benzene and methanol); for inorganic toxic substances, choose Type B (to protect against ammonia) or Type E (to protect against acidic gases, such as hydrogen chloride); for dust, add Type P3 filter cotton.

## 8.3 Eye/face protection

Wear a full-face chemical protective mask. The mask material must be resistant to toxic penetration (such as fluororubber), and the lens must be anti-fog and anti-chemical corrosion.

## 8.4 Skin and body protection

Wear fully enclosed chemical protective clothing. The material must be compatible with toxic substances (such as polyethylene + neoprene composite material); the cuffs and ankles must be tightened and equipped with emergency escape zippers.

## 8.5 Hand protection

Wear toxic and chemical-resistant gloves, preferably made of fluororubber or butyl rubber, with a length of  $\geq 30$  cm, covering the forearm, and change every 4 hours

## 8.6 Hygiene measures

Immediately after the operation, clean the skin with a special detergent (such as a weak alkaline detergent), and then rinse with running water for 15 minutes; clothes need to be disinfected at high temperature (above 60°C) before washing; regular physical examinations (blood routine, liver and kidney function tests every 3 months).

## 9: Physical and chemical properties and safety characteristics

<b>Physical state</b>	Clear Crystals
<b>Colour</b>	COLORLESS LIQ OR WHITE CRYSTALS
<b>Odour</b>	Foul odor above 31.11°C.
<b>Melting point/freezing point</b>	263°C(lit.)
<b>Boiling point or initial boiling point and boiling range</b>	180°C/30mmHg(lit.)
<b>Flammability</b>	Combustible Solid Gives off irritating or toxic fumes (or gases) in a fire.
<b>Lower and upper explosion limit/flammability limit</b>	no data available
<b>Flash point</b>	-6°C(lit.)
<b>Auto-ignition temperature</b>	no data available
<b>Decomposition temperature</b>	no data available
<b>pH</b>	no data available
<b>Kinematic viscosity</b>	no data available
<b>Solubility</b>	In water:Slightly soluble
<b>Partition coefficient n-octanol/water</b>	no data available
<b>Vapour pressure</b>	0.00237mmHg at 25°C
<b>Density and/or relative density</b>	1.392g/mL at 25°C(lit.)
<b>Relative vapour density</b>	no data available
<b>Particle characteristics</b>	no data available

## 10: Stability and reactivity

### 10.1 Reactivity

no data available

### 10.2 Chemical stability

Stable under recommended storage conditions.

### **10.3 Possibility of hazardous reactions**

PROPANE SULTONE reacts slowly with water to give 3-hydroxopropanesulfonic acid. This reaction may be accelerated by acid. May react with strong reducing agents to give toxic and flammable hydrogen sulfide.

### **10.4 Conditions to avoid**

no data available

### **10.5 Incompatible materials**

Evaporation of the residue after treatment of the thietane with hydrogen peroxide is liable to explode, and must be done in an open dish. This is probably because of formation of a 2 or 3-hydroperoxide derivative.

### **10.6 Hazardous decomposition products**

When heated to decomposition propane sultone emits toxic fumes of SO<sub>x</sub>.

## **11: Toxicological information**

### **11.1 Acute toxicity**

Oral: TD Rat oral: 12 g/kg/ 60 wk continuous.

Inhalation: no data available

Dermal: no data available

### **11.2 Skin corrosion/irritation**

no data available

### **11.3 Serious eye damage/irritation**

no data available

### **11.4 Respiratory or skin sensitization**

no data available

### **11.5 Germ cell mutagenicity**

no data available

### **11.6 Carcinogenicity**

The Human Health Assessment Group in EPA's Office of Health and Environmental Assessment has evaluated 1,3-Propane sultone for carcinogenicity. According to their analysis, the weight-of-evidence for 1,3-Propane sultone is group B2, which is based on no evidence in humans and sufficient evidence in animals. As a group B2 chemical, 1,3-Propane sultone is considered as probably carcinogenic to humans.

### **11.7 Reproductive toxicity**

No information is available on the reproductive or developmental effects of 1,3-propane sultone in humans. In the offspring of pregnant rats given a single intravenous injection of 1,3-propane sultone during

gestation, malignant neurogenic tumors and tumors of the pancreas and ovary were reported.

### **11.8 STOT-single exposure**

no data available

### **11.9 STOT-repeated exposure**

no data available

### **11.10 Aspiration hazard**

no data available

## **12: Ecological information**

### **12.1 Toxicity**

Toxicity to fish: no data available

Toxicity to daphnia and other aquatic invertebrates: no data available

Toxicity to algae: no data available

Toxicity to microorganisms: no data available

### **12.2 Persistence and degradability**

No data were located concerning the biodegradation of 1,3-propane sultone either in natural systems or in laboratory studies(SRC). Since 1,3-propane sultone rapidly hydrolyzes in water (1,2), biodegradation probably will not be a significant process in the environment(SRC).

### **12.3 Bioaccumulative potential**

Since 1,3-propane sultone hydrolyzes rapidly in water(1,2), bioconcentration in aquatic organisms is not expected to be a significant process(SRC).

### **12.4 Mobility in soil**

Since 1,3-propane sultone hydrolyzes rapidly in water(1,2), and presumably in moist soil(SRC), adsorption to soil is not expected to be a significant process(SRC).

### **12.5 Other adverse effects**

no data available

## **13: Disposal considerations**

### **13.1 Disposal methods for waste chemicals**

This must be handled by a qualified unit that handles highly toxic waste, using high-temperature incineration (800-1000°C) or chemical neutralization (such as oxidative decomposition) to completely destroy the toxicity. Liquid highly toxic substances must be solidified before incineration. Those that

cannot be incinerated must be stabilized/solidified before being safely landfilled.

## 13.2 Precautions

Disposal personnel must wear fully enclosed chemical protective suits and positive pressure respirators; waste must be strictly classified and packaged to prevent leakage; exhaust gas and wastewater generated during the disposal process must meet discharge standards; mixing with other types of waste is prohibited; and disposal records must be kept for at least 10 years for traceability.

## 14: Transport information

### 14.1 UN Number

ADR/RID: UN2811

IMDG: UN2811

IATA: UN2811

### 14.2 UN Proper Shipping Name

ADR/RID: TOXIC SOLID,  
ORGANIC, N.O.S.

IMDG: TOXIC SOLID,  
ORGANIC, N.O.S.

IATA: TOXIC SOLID, ORGANIC,  
N.O.S.

### 14.3 Transport hazard class(es)

ADR/RID: 6.1

IMDG: 6.1

IATA: 6.1

### 14.4 Packing group, if applicable

ADR/RID: III

IMDG: III

IATA: III

### 14.5 Environmental hazards

ADR/RID: no

IMDG: no

IATA: no

### 14.6 Special precautions for user

no data available

### 14.7 Transport in bulk according to IMO instruments

no data available

## 15: Regulatory information

### 15.1 Safety, health and environmental regulations specific for the product in question

Chemical name	Common names and synonyms	CAS number	EC number
1,3-Propane sultone	1,3-Propane sultone	1120-71-4	214-317-9
New Zealand Inventory of Chemicals (NZIoC)			Listed.
Philippines Inventory of Chemicals and Chemical Substances (PICCS)			Listed.
Vietnam National Chemical Inventory			Not Listed.

<b>Australian Inventory of Industrial Chemicals (AIIC)</b>	Not Listed.
<b>Catalogue of Strictly Restricted Toxic Chemicals in China</b>	Not Listed.
<b>China Catalog of Hazardous chemicals 2015</b>	Not Listed.
<b>European INventory of Existing Commercial chemical Substances</b>	Listed.
<b>IARC Monographs on the Evaluation of Carcinogenic Risks to Humans</b>	Listed.
<b>TSCA Inventory of Chemical Substances</b>	Listed.

## 16: Other information

### Information on revision

**SDS Creation Date** July 1, 2025

**SDS Revision Date** July 1, 2025

### Abbreviations and acronyms in SDS

- CAS: Chemical Abstracts Service
- ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road
- RID: Regulation concerning the International Carriage of Dangerous Goods by Rail
- IMDG: International Maritime Dangerous Goods
- IATA: International Air Transportation Association
- TWA: Time Weighted Average
- STEL: Short term exposure limit
- LC50: Lethal Concentration 50%
- LD50: Lethal Dose 50%
- EC50: Effective Concentration 50%

### SDS References

- IPCS - The International Chemical Safety Cards (ICSC), website: <http://www.ilo.org/dyn/icsc/showcard.home>
- HSDB - Hazardous Substances Data Bank, website: <https://toxnet.nlm.nih.gov/newtoxnet/hsdb.htm>
- IARC - International Agency for Research on Cancer, website: <http://www.iarc.fr/>
- eChemPortal - The Global Portal to Information on Chemical Substances by OECD, website: [http://www.echemportal.org/echemportal/index?pageID=0&request\\_locale=en](http://www.echemportal.org/echemportal/index?pageID=0&request_locale=en)
- CAMEO Chemicals, website: <http://cameochemicals.noaa.gov/search/simple>
- ChemIDplus, website: <http://chem.sis.nlm.nih.gov/chemidplus/chemidlite.jsp>
- ERG - Emergency Response Guidebook by U.S. Department of Transportation, website: <http://www.phmsa.dot.gov/hazmat/library/erg>
- Germany GESTIS-database on hazard substance, website: <http://www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index-2.jsp>
- ECHA - European Chemicals Agency, website: <https://echa.europa.eu/>

**Any questions regarding this Safety Data Sheet, Please send your inquiry to [sales@MolBest.com](mailto:sales@MolBest.com)**

*Disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. We as supplier shall not be held liable for any*

*damage resulting from handling or from contact with the above product.*